

Product Information Sheet

Commission Delegated Regulation (EU) 2019/2013

EPREL registration number: [396195](#)

	Information	Value and precision	Unit
1	Supplier's name or trade mark	GIGABYTE	
2	Supplier's model identifier	AORUS FI25F	
3	Energy efficiency class for standard Dynamic Range (SDR)	F	
4	On mode power demand for Standard Dynamic Range (SDR)	22	W
5	Energy efficiency class (HDR)	G	
6	On mode power demand in High Dynamic Range (HDR) mode	36	W
7	Off mode, power demand	0.3	W
8	Standby mode power demand	n/a	W
9	Networked standby mode power demand	n/a	W
10	Electronic display category	monitor	
11	Size ratio	16:9	
12	Screen resolution (pixels)	1920 x 1080	pixels
13	Screen diagonal	62.2	cm
14	Screen diagonal	25	in
15	Visible screen area	1645	cm ²
16	Panel technology used	LED LCD	

	Information		Value and precision	Unit
17	Automatic Brightness Control (ABC) available		No	
18	Voice recognition sensor available		No	
19	Room presence sensor available		No	
20	Image refresh frequency rate		60 - 240	Hz
21	Minimum guaranteed availability of software and firmware updates (until):		31 12 2022	
22	Minimum guaranteed availability of spare parts (until):		31 12 2022	
23	Minimum guaranteed product support (until):		31 12 2025	
24	Power supply type:		Internal	
i	External standardized power supply (included in the product box)	Standard name	n/a	
		Input voltage	n/a	V AC
		Output voltage	n/a	V DC
ii	External standardized suitable power supply (if not included in the product box)	Standard name	n/a	
		Required output voltage	n/a	V
		Required delivered current	n/a	A
		Required current frequency	n/a	Hz



Der Weltweit erste TACTICAL MONITOR

GIGABYTE AORUS FI25F

Typ	Flat
Panel Größe (Diagonale)	24,5" SS IPS
Display sichtbarer Bereich (HxB) (mm)	543,744*302,616 (mm)
Panel Backlight Typ	Edge
Display Oberfläche	Entspiegelt
Farbraumabdeckung	100% sRGB
Auflösung	1920 X1080 (FullHD)
Helligkeit (cd/m2)	400 cd/m2 (TYP)
Kontrastverhältnis (Typ.)	1000 (TYP)
Kontrastverhältnis (dynamisch)	100M:1
Betrachtungswinkel	178° (H)/178° (V)
Display Farben	8 bits
Reaktionszeit	0,4ms (MPRT)
Bildwiederholrate (Max.)	240Hz
HDR	VESA Display HDR400 / HDMI 2.0 x2
Signal Eingang	Display Port 1.2 x1
Kopfhörer-Anschluss	JA
USB Port(s)	USB 3.0 x2
Active Noise Cancelling (ANC)	JA 1.0
Leistungsaufnahme	65W (Max)
Energiesparmodus	0,5W
Standby-Modus	0,3W
Spannung	AC 100V~240V
Schwenkbar (Winkel)	-5°~+21°
Höhenverstellbar (mm)	130mm
VESA Wandhalterung (mm)	100*100mm
Maße mit Standfuß (LxHxT) (mm)	L558*H485-548*T236
Maße ohne Standfuß (LxHxT) (mm)	L558*H333*T63
Gewicht Produkt (ca.) (kg)	6,66Kg
Gewicht Paket (ca.) (kg)	9,7Kg

