★ Se 海 By Air



仅限货机 CAO





货物运输条件鉴定书

Certification for Safe Transport of Chemical Goods

危险品

样品名称: 锂离子聚合物电池 Li3949T44P8h806459 3.89V 4900mAh/19.06Wh (RATED)

5000mAh/19. 45Wh (TYPICAL)

Sample name: RECHARGEABLE LI-ION POLYMER BATTERY 3. 89V 4900mAh/19. 06Wh (RATED)

5000mAh/19. 45Wh (TYPICAL)

委托单位: 珠海冠宇电池股份有限公司

Zhuhai CosMX Battery Co., Ltd.

生产单位: 珠海冠宇电源有限公司金湾分公司

Zhuhai CosMX Power JinWan Subsidiary Co., Ltd.

Thress Better Life

L海化工院检测有限公司

Shanghai Institute of Chemical Industry Testing Co., Ltd





货物运输条件鉴定书

Certification for Safe Transport of Chemical Goods

Page 1/3

样品 Sample	·名称 e Nam	中文 Chinese	5000mAh/19.45Wh(TYPIC	49T44P8h806459 3.89V 4 CAL.) POLYMER BATTERY 3.89V	4900mAh/19.06Wh(RATED		
委托单位 Consignor			珠海冠宇电池股份有限公司 Zhuhai CosMX Battery Co., Ltd.				
生产单位 Manufacturer			珠海冠宇电源有限公司金湾分公司 Zhuhai CosMX Power JinWan Subsidiary Co., Ltd.				
检验方法、程序 Inspection method and procedure							
样品外观 Sample appearance			银色, 黄色双色铝塑外壳 Silvery and yellow Aluminum-plastics shell				
包装件信息 Package information			锂电池总净重≤10kg。 Lithium batteries total net weight≤10kg.				
序号 NO.		电池种类 Battery type	型号 Model	容量Capacity /锂含量Li content	放置方式 Placement	单颗重量kg Unit weight	数量 Quantity
1	池	1锂聚合物单电芯电 .Rechargeable lymer single coll battery		4900mAh/19.06Wh	电池单独运输 Battery only	0.067	117
鉴定结论	I DENTI FI CATI ON CONCL USI ON	Shipping name:Lit Class or division UN Number:UN3480 3. 包装要求(Pac 按包装说明965第11	Ekaging requirement B部分要求办理。 Ckaged according to th	s) me Packaging Instruction	on 965 section IB.		DGR)
各.	注	Inspection Date	2022-02-24	2022-02-24	Effective Date: 202	2-02-24	

批准 Approver: 毛星

审核 Checker: 童学收





Page 2/3


序号	检验结果及其他事项							
No.	Inspection results and other things							
1	本报告所述锂电池按照《危险品规则》(63版)[以下简称DGR] 3.9.2.6.1(e)规定的质量管理体系进行制造。 本报告所述锂电池不属于因安全原因召回的锂电池。 本报告所述锂电池不进行以回收或处置为目的的航空运输,不属于废弃锂电池。 Lithium cells and batteries listed in this report were manufactured under the quality management program described in IATA DGR 63rd 3.9.2.6.1(e). Lithium cells and batteries listed in this report are not the defective cells or batteries returned to the manufacturer for safety reasons. Lithium cells and batteries listed in this report are not waste lithium cells or batteries, and they will not be shipped for recycling or disposal.							
2	本报告所述锂电池已通过《联合国试验和标准手册》第111部分38.3小节相应测试要求。 包装件能够承受1.2m跌落试验。 Lithium cells and batteries listed in this report are of the types proved to meet the requirements of each applicable test in the UN Manual of Tests and Criteria, Part 111, sub-section 38.3. The package has passed the 1.2m drop test. UN38.3试验概要编号 The UN38.3 Test Summary No.(s) 812200700512183 详细信息请扫描右侧二维码。 Please scan the QR code on the right for more information.							
3	锂电池完全封装在内包装内,位于坚固的刚性外包装中。 电池具有适当的防短路措施。 Lithium cells and batteries are packed in inner packagings that completely enclose the cell or battery and placed in a strong rigid outer packaging. Cells and batteries are properly protected to prevent short circuits.							
1	接DGR IB部分托运的电池必须根据第8部分规定在托运人中报单中描述,并且当使用航空货运单时,货运单必须包含8.2.1和8.2.2中相关 近用要求。 Cells or batteries shipped under the provisions of Section IB in IATA DGR must be described on a Shipper's Declaration as set out in Section 8, and the air waybill, when used, must contain the applicable information required by 8.2.1 and 8.2.2.							
5	除使用9类锂电池危险性标签(DGR图7.3.X)外,每个包装件必须按DGR图7.1.C所示做耐久清晰的标记。 每个包装件必须按DGR7.1.4.1(a)和(b)要求标记,此外当7.1.4.1(c)有要求时还必须标明包装件净重。 每个包装件必须贴有"仅限货机"标签(DGR图7.4.B)。 Each package must be durably and legibly marked with the mark shown in Figure 7.1.C in IATA DGR in addition to the Class 9-Lithium Battery hazard label (Figure 7.3.X in IATA DGR). Each package must be marked in accordance with the requirements of 7.1.4.1(a) and (b) in IATA DGR and in addition the net weight when required by 7.1.4.1(c) must be marked on the package. Each package must be labelled with the "Cargo Aircraft Only" label(Figure 7.4.B in IATA DGR).							
6	根据委托单位声明,本报告所述锂离子电池交付运输时,其荷电状态必须不超过额定容量的30%。 According to the statement of the consignor, lithium ion cells and batteries listed in this report must be offered for transport at a state of charge (SoC) not exceeding 30% of their rated capacity.							
7	电池不得与第1类爆炸品(1.4S项除外), 2.1项易燃气体,第3类易燃液体,4.1项易燃固体或5.1项氧化性物质等危险品包装在同一外包装或集合包装内。 Cells and batteries must not be packed in the same outer packaging or overpack with dangerous goods classified in Class 1 (explosives) other than Division 1.4S, Division 2.1 (flammable gases), Class 3 (flammable liquids), Division 4.1 (flammable solids) or Division 5.1 (oxidizers).							
	-验证码: 237962-							





货物运输条件鉴定书


Certification for Safe Transport of Chemical Goods













额定容量/RATED CAPACITY: 4900mAh(19.06Wh) 典型容量/TYPICAL CAPACITY: 5000mAh(19.45Wh)

标称电压/NOMINAL VOLTAGE: 3.89V==

充电限制电压/LIMITED CHARGE VOLTAGE: 4.48V之 型号/MODEL: Li3949T44P8h806459

